



Key, MS2-20, according to data

Part no. M22-ES-MS*
Catalog No. 216417
Eaton Catalog No. -
EL-Nummer 4355424
(Norway)

Delivery program

Product range			Accessories
Part group reference (e.g. DIL)			M22
Basic function accessories			Individual keys
Single unit/Complete unit			Single unit
Description			Lock mechanism MS2 – MS20
Degree of Protection			IP66
Connection to SmartWire-DT			no
For use with			M22(S)-W(R)S(3)-MS*...
Note asterisk part number			Please configure the asterisks in the cart

Technical data

General

Degree of Protection			IP66
Ambient temperature			
Open		°C	-25 - +70

Design verification as per IEC/EN 61439

Technical data for design verification			
Operating ambient temperature min.		°C	-25
Operating ambient temperature max.		°C	70

Technical data ETIM 6.0

Low-voltage industrial components (EG000017) / Accessories for control circuit devices (EC002024)			
Electric engineering, automation, process control engineering / Low-voltage switch technology / Low-voltage switch technology (accessories) / Control circuit devices (accessories) (ec1@ss8.1-27-37-92-16 [AC0043008])			
Type of electrical accessory			-
Type of mechanical accessory			Key

Approvals

North America Certification			UL/CSA certification not required
-----------------------------	--	--	-----------------------------------