



CorePro LED PLC

CorePro LED PLC 6.5W 840 4P G24q-2

Philips CorePro LED PLC is the ideal uplampping solution for downlights in a wide range of general lighting applications. It integrates a LED light source into a traditional fluorescent form factor to offer superb energy savings over a lifetime that's twice as long as fluorescent alternatives.

Product data

General Information		Power Factor (Nom)	
Cap-Base	G24Q-2 [G24q-2]		0.9
Nominal Lifetime (Nom)	30000 h	Voltage (Nom)	20-50 V
Switching Cycle	50000X	Temperature	
B50L70	30000 h	T-Ambient (Max)	35 °C
		T-Ambient (Min)	-20 °C
		T-Storage (Max)	65 °C
		T-Storage (Min)	-40 °C
		T-Case Maximum (Nom)	66 °C
		Controls and Dimming	
		Dimmable	No
		Mechanical and Housing	
		Product Length	100 mm
		Approval and Application	
		Energy Saving Product	Yes
		Energy Efficiency Label (EEL)	A+
		Approval Marks	TUV CE marking RoHS compliance KEMA Keur certificate
Light Technical			
Color Code	840 [CCT of 4000K]		
Luminous Flux (Nom)	700 lm		
Luminous Flux (Rated) (Nom)	700 lm		
Correlated Color Temperature (Nom)	4000 K		
Color Consistency	<6		
Color Rendering Index (Nom)	83		
LLMF At End Of Nominal Lifetime (Nom)	70 %		
Operating and Electrical			
Input Frequency	30000-80000 Hz		
Power (Rated) (Nom)	6.5 W		
Lamp Current (Max)	300 mA		
Lamp Current (Min)	150 mA		
Starting Time (Nom)	0.5 s		
Warm Up Time To 60% Light (Nom)	0.5 s		

CorePro LED PLC


Energy Consumption kWh/1000 h	9 kWh
Product Data	
Full product code	871869654121000
Order product name	CorePro LED PLC 6.5W 840 4P G24q-2
EAN/UPC - Product	8718696541210
Order code	929001201102

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001201102
Net Weight (Piece)	0.078 kg

Warnings and Safety

- NOTES: The overall energy efficiency and light distribution of any installation that uses these lamps are determined by the design of the installation.


Dimensional drawing




LEDtube PLC 6.5W G24q-2/840 4P

Product	D1	D2	A1	A2	A3
CorePro LED PLC 6.5W 840 4P G24q-2	24.3 mm	28.4 mm	105.8 mm	125 mm	140.6 mm

Photometric data



General Uniform Lighting
PLC 100mm 9W G24Q-3 840 1000lm
Page 10



LEDtube PLC 100mm 9W G24Q-3 840 1000lm

CorePro LED PLC

