



CorePro LEDtube InstantFit HF

CorePro LEDtube HF 1500mm 20W865 T8 G

CorePro LEDtube InstantFit HF is an affordable LED solution suitable for replacing T8 fluorescent lamps. It provides a natural lighting effect for use in general lighting applications, as well as instant energy savings – an environmentally friendly solution.

Product data

General Information	
Cap-Base	G13 [Medium Bi-Pin Fluorescent]
Nominal Lifetime (Nom)	30000 h
Switching Cycle	50000X
B50L70	30000 h
Light Technical	
Color Code	865 [CCT of 6500K]
Beam Angle (Nom)	240 °
Luminous Flux (Nom)	2000 lm
Luminous Flux (Rated) (Nom)	2000 lm
Color Designation	Cool Daylight
Rated Beam Angle	240 °
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	100 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	83
LLMF At End Of Nominal Lifetime (Nom)	70 %

Operating and Electrical	
Input Frequency	20000-75000 Hz
Power (Rated) (Nom)	20 W
Lamp Current (Max)	700 mA
Lamp Current (Min)	200 mA
Wattage Equivalent	58 W
Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.9
Voltage (Nom)	30-80 V
Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
T-Case Maximum (Nom)	55 °C

CorePro LEDtube InstantFit HF

Controls and Dimming

Dimmable	No
----------	----

Mechanical and Housing

Product Length	1500 mm
----------------	---------


Approval and Application

Energy Saving Product	Yes
Suitable For Accent Lighting	No
Energy Efficiency Label (EEL)	A+
Approval Marks	TUV CE marking RoHS compliance KEMA Keur certificate
Energy Consumption kWh/1000 h	25 kWh

Product Data

Full product code	871869659205200
Order product name	CorePro LEDtube HF 1500mm 20W865 T8 G
EAN/UPC - Product	8718696592052
Order code	929001249802
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001249802
Net Weight (Piece)	0.270 kg



Dimensional drawing



TLED 20W-58W 2000lm 240D 6500K G13 ND

Product	D	A1	A2	A3
CorePro LEDtube HF 1500mm 20W865 T8 G	27.9 mm	1500 mm	1505.9 mm	1514.2 mm

Photometric data



CorePro LEDtube InstantFit HF

