



MASTER LEDtube InstantFit HF T5

MAS LEDtube HF 1500mm UO 36W 830 T5

Philips MASTER LEDtube InstantFit T5 integrates a LED light source into a traditional fluorescent form factor. Its unique design creates a perfectly uniform visual appearance which cannot be distinguished from traditional fluorescent. The Philips MASTER LEDtube InstantFit T5 is the ideal solution for customers who have higher light output requirements and want to maximize value over lifetime. Full energy savings & longer lifetime result in attractive payback times and TCO benefits.

Product data

General Information	
Cap-Base	G5 [G5]
Nominal Lifetime (Nom)	50000 h
Switching Cycle	50000X
B50L70	50000 h
Light Technical	
Color Code	830 [CCT of 3000K]
Luminous Flux (Nom)	5200 lm
Luminous Flux (Rated) (Nom)	5200 lm
Correlated Color Temperature (Nom)	3000 K
Color Consistency	<6
Color Rendering Index (Nom)	83
LLMF At End Of Nominal Lifetime (Nom)	70 %
Operating and Electrical	
Input Frequency	40000-75000 Hz

Power (Rated) (Nom)	36 W
Lamp Current (Max)	750 mA
Lamp Current (Min)	550 mA
Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	0.5 s
Voltage (Nom)	65-75 V
Temperature	
T-Ambient (Max)	45 °C
T-Ambient (Min)	-20 °C
T-Storage (Max)	65 °C
T-Storage (Min)	-40 °C
Controls and Dimming	
Dimmable	No

MASTER LEDtube InstantFit HF T5

Mechanical and Housing

Product Length 1500 mm

Approval and Application

Energy Saving Product Yes

Energy Efficiency Label (EEL) A++

Approval Marks TUV CE marking RoHS compliance KEMA Keur certificate

Energy Consumption kWh/1000 h 42 kWh

Product Data

Full product code 871869670599500

Order product name MAS LEDtube HF 1500mm UO 36W 830 T5

EAN/UPC - Product 8718696705995

Order code 929001346102


Numerator - Quantity Per Pack 1

Numerator - Packs per outer box 10

Material Nr. (12NC) 929001346102

Net Weight (Piece) 0.170 kg



Dimensional drawing



Product	D1	D2	A1	A2	A3
MAS LEDtube HF 1500mm UO 36W 830 T5	15.2 mm	21 mm	1447.8 mm	1454.9 mm	1462 mm

TLED 230V 37-80W 5600lm 160D 3000K G5 ND

Photometric data




MASTER LEDtube InstantFit HF T5

Photometric data




LEDtube VLE 600 mm 10 W /830 T8 ROT

Lifetime




LEDtube 1500mm 36W G5 5600lm



LEDtube 1200mm 26W G5 3900lm

MASTER LEDtube InstantFit HF T5

Lifetime



LEDtube 1500mm 36W G5 5600lm

