



Series connection time switch 7 days, series connection time switch, autonomy, 3 TLE

Part no. TSQW1CO
Catalog No. 167392
Eaton Catalog No. TSQW1CO
EL-Nummer 1456992
(Norway)

Design verification as per IEC/EN 61439

| Technical data for design verification | | | |
|--|------------|----|-----|
| Rated operational current for specified heat dissipation | I_n | A | 0 |
| Heat dissipation per pole, current-dependent | P_{vid} | W | 0 |
| Equipment heat dissipation, current-dependent | P_{vid} | W | 0 |
| Static heat dissipation, non-current-dependent | P_{vs} | W | 0.5 |
| Heat dissipation capacity | P_{diss} | W | 0 |
| Operating ambient temperature max. | | °C | -20 |
| Operating ambient temperature max. | | °C | 55 |
| | | | 0 |

Technical data ETIM 6.0

| Devices for distribution board-/surface mounting (EG000062) / Analogous time switch for distribution board (EC002304) | | | |
|--|--|-----|---------------------|
| Electric engineering, automation, process control engineering / Measurement technology, process measurement technology / Measuring appliance, time / Analogous time switch (ecl@ss8.1-27-20-01-09 [ACN651008]) | | | |
| Mounting method | | | DIN rail |
| Number of channels | | | 1 |
| Supply voltage | | V | 110 - 230 |
| Voltage type of supply voltage | | | AC |
| Frequency supply voltage | | Hz | 45 - 60 |
| Autonomy in hours | | | 200 |
| Autonomy in years | | | 0 |
| Autonomy per day | | s | 1 |
| 60 min. program | | | No |
| 24 h program | | | No |
| Weekly program | | | Yes |
| Annual program | | | No |
| Mains synchronous | | | No |
| Quartz controlled | | | Yes |
| Contact type | | | Change-over contact |
| Shortest switching time channel 1 | | min | 120 |
| Shortest switching time channel 2 | | min | 0 |
| Program shift divide 1 | | min | 120 |
| Program shift divide 2 | | min | 0 |
| Automatic switching summer-/winter time | | | No |
| Manual operation | | | Yes |
| Switching preselection | | | Yes |
| Nominal switching current at 250 V AC | | A | 16 |
| Potential free switch contact | | | Yes |
| Degree of protection (IP) | | | IP20 |
| Width in number of modular spacings | | | 3 |
| Width | | mm | 52.5 |
| Height | | mm | 90 |
| Depth | | mm | 60 |