

Installation relay, 230VAC/50Hz, 1N/O+1N/C, 20A, 1HP



Part no. Z-R230/S0

Catalog No. 265181

**EL-Nummer 4133967
(Norway)**

Design verification as per IEC/EN 61439

Technical data for design verification		
Operating ambient temperature max.	°C	-20
Operating ambient temperature max.	°C	45

Technical data ETIM 6.0

Devices for distribution board-/surface mounting (EG000062) / Installation relay (EC001652)

Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Installation relay for distribution board (ec1@ss8.1-27-14-23-09 [AFZ821011])

Function		Mechanical
Mounting method		DIN rail
Width in number of modular spacings		1
Built-in depth	mm	60
Number of normally open contacts		1
Number of normally closed contacts		1
Number of change-over contacts		0
Control voltage 1	V	230 - 230
Type of control voltage 1		AC
Frequency control voltage 1	Hz	50 - 50
Control voltage 2	V	0 - 0
Type of control voltage 2		-
Frequency control voltage 2	Hz	0 - 0
Nominal rated current	A	20
Supply voltage	V	250 - 250
Voltage type of supply voltage		AC
Max. incandescent lamp load	W	0
Max. load fluorescent lamp	VA	0
Max. load fluorescent lamp (Duo circuit)	VA	0
Max. load fluorescent lamp (parallel compensated)	VA	0
Max. switching current (cos phi = 0.6)	A	0

Dimensions

