



Main switch, 240 V, 32A, 4HP

Part no. IS-32/4
Catalog No. 276269
Eaton Catalog No. IS-32/4

Similar to illustration

Delivery program

| | | | |
|------------------|-------|---|--|
| Basic function | | | Main load disconnecter switch |
| Number of poles | | | 4 pole |
| Application | | | Switchgear for industrial and advanced commercial applications |
| Rated current | I_n | A | 32 |
| Product range | | | IS |
| Contact sequence | | | |

Design verification as per IEC/EN 61439

| | | | |
|--|--|----|----|
| Technical data for design verification | | | |
| Operating ambient temperature max. | | °C | -5 |
| Operating ambient temperature max. | | °C | 40 |

Technical data ETIM 6.0

| | | | |
|---|--|----|----------------|
| Devices for distribution board-/surface mounting (EG000062) / Main switch for distribution board (EC001545) | | | |
| Electric engineering, automation, process control engineering / Electrical installation, device / Modular serial built-in device for electrical circuit distributors / Main switch for distribution board (ecl@ss8.1-27-14-23-01 [AFZ813011]) | | | |
| Switching function | | | - |
| Number of normally open contacts | | | 0 |
| Number of normally closed contacts | | | 0 |
| Number of change-over contacts | | | 0 |
| Number of poles | | | 4 |
| Nominal rated current | | A | 32 |
| Nominal rated voltage | | V | 240 |
| Min. rated voltage | | V | 240 |
| Rated switching capacity | | kA | 0 |
| Short-circuit breaking capacity (Icw) | | kA | 2 |
| Voltage type | | | AC |
| Forced segregation (according to DIN VDE 0113) | | | No |
| With signal lamp | | | No |
| Colour calotte | | | Not applicable |
| Lamp type | | | Not applicable |
| Lamp socket | | | Not applicable |
| Max. lamp power | | W | 0 |
| Width in number of modular spacings | | | 4 |
| Built-in depth | | mm | 69.5 |
| Degree of protection (IP) | | | IP40 |

Dimensions

