



Miniature circuit breaker (MCB), 4A, 1p, C-Char, DC current

Part no. FAZ-C4/1-DC
Catalog No. 279124
Eaton Catalog No. FAZ-C4/1-DC
EL-Nummer 1691490
(Norway)

Similar to illustration

Delivery program

Basic function			Miniature circuit-breakers
Number of poles			1 pole
Tripping characteristic			C
Application			Switchgear for DC applications
Rated current	I_n	A	4
Rated switching capacity acc. to IEC/EN 60947-2		kA	10
Product range			FAZ-DC

Technical data

Electrical

Standards			IEC/EN 60947-2
Rated operational voltage	U_e	V	
		V DC	250 (per pole)
Rated switching capacity acc. to IEC/EN 60947-2		kA	10
Characteristic			C
Max. back-up fuse		A gL/gG	100
Selectivity Class			3
Lifespan	Operations		> 10000
Direction of incoming supply			Polarity dependent

Mechanical

Standard front dimension		mm	45
Enclosure height		mm	80
Terminal protection			Finger and back-of-hand proof to BGV A2
Mounting width per pole		mm	17.5
Mounting			IEC/EN 60715 top-hat rail
Degree of Protection			IP20, IP40 (when fitted)
Terminals top and bottom			Twin-purpose terminals
Terminal capacities		mm ²	
		mm ²	1 x 25
		mm ²	2 x 10
Thickness of busbar material		mm	0.8 ... 2
Mounting position			As required


Design verification as per IEC/EN 61439

Technical data for design verification			
Rated operational current for specified heat dissipation	I_n	A	4
Heat dissipation per pole, current-dependent	P_{vid}	W	0
Equipment heat dissipation, current-dependent	P_{vid}	W	1.4
Static heat dissipation, non-current-dependent	P_{vs}	W	0
Heat dissipation capacity	P_{diss}	W	0
Operating ambient temperature max.		°C	-40
Operating ambient temperature max.		°C	75
			linear, per +1 °C, results in a 0.5% reduction of current carrying capacity

Technical data ETIM 6.0

Circuit breakers and fuses (EG000020) / Miniature circuit breaker (MCB) (EC000042)				
Electric engineering, automation, process control engineering / Electrical installation, device / Miniature circuit breaker system (MCB) / Miniature circuit breaker (MCB) (ecI@ss8.1-27-14-19-01 [AAB905011])				
Release characteristic				C
Number of poles (total)				1
Number of protected poles				1
Nominal rated current		A		4
Nominal rated voltage		V		250
Rated short-circuit breaking capacity Icn EN 60898 at 230 V		kA		0
Rated short-circuit breaking capacity Icn EN 60898 at 400 V		kA		0
Rated short-circuit breaking capacity Icu IEC 60947-2 at 230 V		kA		10
Rated short-circuit breaking capacity Icu IEC 60947-2 at 400 V		kA		10
Voltage type				DC
Current limiting class				3
Frequency		Hz		50 - 60
Concurrently switching N-neutral				No
Suitable for flush-mounted installation				No
Over voltage category				3
Pollution degree				2
Width in number of modular spacings				1
Built-in depth		mm		70.5
Additional equipment possible				Yes
Degree of protection (IP)				IP20

Dimensions



Additional product information (links)

AWA1220-1755 Circiut-breaker	
AWA1220-1755 Circiut-breaker	http://ftp.moeller.net/DOCUMENTATION/AWA_INSTRUCTIONS/17550701.pdf

