



- Low profile 4.8cm height
- Unique elegant design
- Easy to install
- Compliant to EN 60 598-2-22
- Certificated by ENEC Kema Keur
- IP rating IP42
- High temperature batteries Ni-Cd
- Opal diffuser version (EL5)
- Autotest version

Light Source:

6W FL6WT5

Construction:

Base, mounting plate and cover, fire retardant ABS, lens optical grade acrylic

Operation:

Maintained and Non-Maintained

Applications:

Residential applications, offices, hotels, restaurants, schools

Cronus 6W is a compact low profile luminaire with a stylish design which offers an attractive emergency lighting solution for a wide variety of areas.

An additional small incandescence lamp is embodied in Cronus 6W indicating the normal charging mode while providing a smart night light solution.

A full range of accessories are available. These include a recessed base for wall or flush mounting, a plexiglass sign for installing the luminaire as an exit sign, as well as the opal diffuser version.




O-EL5



O-EL8RB



O-EL8PSLR



Model	Height (m)	Distance for 1 Lux				Distance for 0,5 Lux			
O-EL6									
	02,60	02,32	06,95	01,96	05,58	03,98	08,32	03,29	07,16
	02,80	02,22	07,17	01,92	05,62	04,08	08,62	03,31	07,35
	03,00	02,03	07,25	01,85	05,65	04,13	08,90	03,33	07,46
	03,20	01,89	06,98	01,75	05,68	03,99	09,24	03,34	07,63
	03,50	01,56	06,62	01,56	05,65	03,81	09,63	03,32	07,77
	04,00	00,89	06,18	00,92	05,40	03,59	10,20	03,20	08,00

Order code	Description					
O-EL5	Cronus 6W NM 90min with Opal diffuser	FL6W T5		90'	2,4V-1,5Ah NiCd	Non-Maintained
O-EL6	Cronus 6W NM 90min	FL6W T5	60 Lm	90'	2,4V-1,5Ah NiCd	Non-Maintained
O-EL6-3H	Cronus 6W NM 180min	FL6W T5	70 Lm	180'	6V-1,5Ah NiCd	Non-Maintained
Accessories						
O-EL6PSLR	Double side exit sign (Left/Right)					
O-EL6PSD	Double side exit sign (Down)					
O-EL6RB	Recessed base (both for wall or flush mounting)					