



# CorePro LEDspot MV

## Corepro LEDspot CLA 4.6-50W GU10 865 36D

CorePro LEDspots are a perfect fit for spot lighting and deliver warm halogen-like light. They are compatible with most existing fixtures with a GU10 and are designed as a retrofit replacement for halogen or incandescent spots. CorePro LEDspots deliver significant energy savings and minimize maintenance cost.

### Product data

General Information	
Cap-Base	GU10 [ GU10]
Nominal Lifetime (Nom)	15000 h
Switching Cycle	50000X
Technical Type	4.6-50W
Light Technical	
Color Code	865 [ CCT of 6500K]
Beam Angle (Nom)	36 °
Luminous Flux (Nom)	390 lm
Luminous Flux (Rated) (Nom)	390 lm
Luminous Intensity (Nom)	770 cd
Color Designation	Cool Daylight
Rated Beam Angle	36 °
Correlated Color Temperature (Nom)	6500 K
Luminous Efficacy (rated) (Nom)	84.78 lm/W
Color Consistency	<6
Color Rendering Index (Nom)	80
LLMF At End Of Nominal Lifetime (Nom)	70 %
Luminous Flux In 90° Cone (Rated)	390 lm

Operating and Electrical	
Input Frequency	50 to 60 Hz
Power (Rated) (Nom)	4.6 W
Lamp Current (Nom)	39 mA
Wattage Equivalent	50 W
Starting Time (Nom)	0.5 s
Warm Up Time To 60% Light (Nom)	0.5 s
Power Factor (Nom)	0.5
Voltage (Nom)	220-240 V
Temperature	
T-Case Maximum (Nom)	78 °C
Controls and Dimming	
Dimmable	No
Approval and Application	
Suitable For Accent Lighting	Yes
Energy Efficiency Label (EEL)	A++
Energy Consumption kWh/1000 h	5 kWh


# CorePro LEDspot MV

## Product Data

Full product code	871869672841300
Order product name	Corepro LEDspot CLA 4.6-50W GU10 865 36D
EAN/UPC - Product	8718696728413
Order code	929001218302
Numerator - Quantity Per Pack	1

Numerator - Packs per outer box	10
Material Nr. (12NC)	929001218302
Net Weight (Piece)	0.038 kg


## Dimensional drawing




GU10 230V 4W-35W 260lm 100D 4000K GU10ND

Product	D	C
Corepro LEDspot CLA 4.6-50W GU10 865 36D	50 mm	54 mm

## Photometric data



Technical Information 1 Philips Lighting B.V. Page 1/7



CorePro LEDspotMV 50W GU10 865 36D

