



MASTER VALUE LEDspot LV

MAS LED spot VLE D 5.5-35W MR16 840 60D

Philips MASTER VALUE MR16 is the series of Low Voltage (12VAC) Halogen MR16 replacements. Not only does it employ Philips' patented solution to guarantee the broadest possible compatibility with standard 12V Halogen electronic transformers. It also delivers beam intensity which is equivalent to the 50W Philips Halogen MR16 lamps. The form-factor of Philips MASTER Value LED MR16 guarantees a 100% form on the back-side of the lamp (exact form with Halogen lamps.)

Product data

General Information		Color Rendering Index (Nom)	
Cap-Base	GU5.3 [GU5.3]	80	
Nominal Lifetime (Nom)	25000 h	LLMF At End Of Nominal Lifetime (Nom) 70 %	
Switching Cycle	50000X	Luminous Flux In 90° Cone (Rated) 490 lm	
Technical Type	5.5-35W		
Light Technical		Operating and Electrical	
Color Code	840 [CCT of 4000K]	Power (Rated) (Nom)	5.5 W
Beam Angle (Nom)	60 °	Lamp Current (Nom)	630 mA
Luminous Flux (Nom)	490 lm	Wattage Equivalent	35 W
Luminous Flux (Rated) (Nom)	490 lm	Starting Time (Nom)	0.5 s
Luminous Intensity (Nom)	550 cd	Warm Up Time To 60% Light (Nom)	0.5 s
Color Designation	Cool White (CW)	Power Factor (Nom)	0.8
Rated Beam Angle	60 °	Voltage (Nom)	ac Electronic 12 V
Correlated Color Temperature (Nom)	4000 K	Temperature	
Luminous Efficacy (rated) (Nom)	89.09 lm/W	T-Case Maximum (Nom)	95 °C
Color Consistency	<6		

MASTER VALUE LEDspot LV


Controls and Dimming	
Dimmable	Yes
Approval and Application	
Suitable For Accent Lighting	Yes
Energy Efficiency Label (EEL)	A+
Energy Consumption kWh/1000 h	7 kWh
Product Data	
Full product code	871869670833000

Order product name	MAS LED spot VLE D 5.5-35W MR16 840 60D
EAN/UPC - Product	8718696708330
Order code	929001326402
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001326402
Net Weight (Piece)	0.045 kg

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights



Dimensional drawing



MR16 12V 5W-35W 410lm 60D 4000K GU5.3 D

Product	D	C
MAS LED spot VLE D 5.5-35W MR16 840 60D	50.5 mm	45 mm

Photometric data



MAS VLE LEDspotLV 35W GU5-3 840 36D MR16

MASTER VALUE LEDspot LV

