



MASTER VALUE LEDspot LV

MAS LED spot VLE D 7-50W MR16 827 60D

Philips MASTER VALUE MR16 is the series of Low Voltage (12VAC) Halogen MR16 replacements. Not only does it employ Philips' patented solution to guarantee the broadest possible compatibility with standard 12V Halogen electronic transformers. It also delivers beam intensity which is equivalent to the 50W Philips Halogen MR16 lamps. The form-factor of Philips MASTER Value LED MR16 guarantees a 100% form on the back-side of the lamp (exact form with Halogen lamps.)

Product data

General Information		Color Rendering Index (Nom)	
Cap-Base	GU5.3 [GU5.3]	LLMF At End Of Nominal Lifetime (Nom)	70 %
Nominal Lifetime (Nom)	25000 h	Luminous Flux In 90° Cone (Rated)	621 lm
Switching Cycle	50000X	Operating and Electrical	
Technical Type	7-50W	Power (Rated) (Nom)	7 W
Light Technical		Lamp Current (Nom)	760 mA
Color Code	827 [CCT of 2700K]	Wattage Equivalent	50 W
Beam Angle (Nom)	60 °	Starting Time (Nom)	0.5 s
Luminous Flux (Nom)	621 lm	Warm Up Time To 60% Light (Nom)	0.5 s
Luminous Flux (Rated) (Nom)	621 lm	Power Factor (Nom)	0.8
Luminous Intensity (Nom)	800 cd	Voltage (Nom)	ac Electronic 12 V
Color Designation	Warm White (WW)	Temperature	
Rated Beam Angle	60 °	T-Case Maximum (Nom)	105 °C
Correlated Color Temperature (Nom)	2700 K		
Luminous Efficacy (rated) (Nom)	88.71 lm/W		
Color Consistency	<6		

MASTER VALUE LEDspot LV


Controls and Dimming	
Dimmable	Yes
Approval and Application	
Suitable For Accent Lighting	Yes
Energy Efficiency Label (EEL)	A+
Energy Consumption kWh/1000 h	8 kWh
Product Data	
Full product code	871869670841500

Order product name	MAS LED spot VLE D 7-50W MR16 827 60D
EAN/UPC - Product	8718696708415
Order code	929001326802
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	929001326802
Net Weight (Piece)	0.045 kg

Warnings and Safety

- Operating temperature range is between -20° C and 45° C ambient
- Only to apply in dry or damp locations and most of open fixtures with lamp-holders that offer sufficient space (10 mm free air space)
- Not intended for use with emergency light fixtures or exit lights



Dimensional drawing



MR16 12V 7.5W-50W 60D 2700K GU5.3 D

Product	D	C
MAS LED spot VLE D 7-50W MR16 827 60D	50.5 mm	49.5 mm

Photometric data



MAS VLE LEDspotLV 35W GU5-3 827 36D MR16

MASTER VALUE LEDspot LV

