

## NWS 109-49-VDE-180 High Leverage Combination Pliers CombiMax



## **High Leverage Combination Pliers CombiMax VDE**

American pattern

For holding, gripping, bending and cutting work

For cutting hard and soft wires

Cutting edges inductively hardened

Asymmetric inside jaws for better grip on the workpiece

Gripping zones for flat and round materials

With Nail- & wire holder

Integrated ring spanner

Power transmission with optimum leverage for easy and effortless work

Handles with ergonomically shaped SoftGripp multicomponent safety sleeves according to DIN EN/IEC 60900 Made of tool steel, forged, oil-hardened

SKU: 109-49-VDE-180

Ean Code: 40 03758 40937 4

<b>▼</b> ►	Length in millimetres	180
4 ▶	Length in inches	7
	Jaw shape	Ш
	Cutting edge shape	
•	Soft wire - 220 N/mmí«_ copper, aluminium, plastic - cutting value in millimetres	5,2
•	nail, wire nail - cutting value in millimetres	3,4
•	Hard wire - 1800 N/mmí«_ wire rope fibre, steel rope - cutting value in millimetres	2,2
8	Cable - Al + Cu multi-wired conductor single and stranded conductor - cutting value in millimetres	12
$\Diamond$	Size of ring spanner in millimetres	18
DIN	DIN standards - National, European and worldwide	DIN ISO 5746
800	Design	<b>&amp;</b> ₩
4	Weight in Grams	260



www.filippidisandsons.gr