



# Ledinaire floodlights gen3

## BVP165 LED240/865 PSU 200W SWB CE

-- 865 cool daylight -- Symmetrical

This Ledinaire floodlights range contains a selection of popular off-the-shelf LED luminaires that comes with the Philips high quality levels at a competitive price. Reliable, energy-efficient and affordable – just what you need.

### Product data

General Information	
Lamp family code	-
Light source color	865 cool daylight
Light source replaceable	No
Number of gear units	1 unit
Driver/power unit/transformer	-
Driver included	Yes
Optical cover/lens type	Glass
Luminaire light beam spread	110° x 110°
Control interface	-
Connection	Flying leads/wires
Cable	Cable 2.0 m without plug
Protection class IEC	Safety class I
Flammability mark	-
CE mark	CE mark
ENEC mark	-
Warranty period	3 years
Optic type outdoor	Symmetrical
Constant light output	No

Number of products on MCB of 16 A type B	11
Photobiological risk	Photobiological risk group 1 @ 200mm to EN62471
Photobiological risk specification	0.2 m
EU RoHS compliant	Yes
Light source engine type	LED
Service tag	No

### Light Technical

Upward light output ratio	0
Standard tilt angle posttop	-
Standard tilt angle side entry	-

### Operating and Electrical

Input Voltage	220 to 240 V
Input Frequency	50 or 60 Hz
Initial CLO power consumption	- W
Average CLO power consumption	200 W
End CLO power consumption	- W

## Ledinaire floodlights gen3

Inrush current	4.38 A
Inrush time	0.0284 ms
Power Factor (Min)	0.95

### Controls and Dimming

Dimmable	No
----------	----

### Mechanical and Housing

Housing Material	Aluminum die cast
Reflector material	Polycarbonate
Optic material	Glass
Optical cover/lens material	Tempered glass
Fixation material	Steel
Mounting device	Mounting bracket adjustable
Optical cover/lens shape	Flat
Optical cover/lens finish	Clear
Overall length	336 mm
Overall width	482 mm
Overall height	35.7 mm
Effective projected area	0.112 m <sup>2</sup>
Color	grey
Dimensions (Height x Width x Depth)	36 x 482 x 336 mm (1.4 x 19 x 13.2 in)

### Approval and Application

Ingress protection code	IP65 [ Dust penetration-protected, jet-proof]
Mech. impact protection code	IK07 [ 2 J reinforced]
Surge Protection (Common/Differential)	4/4 kV

### Initial Performance (IEC Compliant)

Initial luminous flux (system flux)	24000 lm
Luminous flux tolerance	+/-10%

Initial LED luminaire efficacy	120 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>80
Initial chromaticity	(0.313, 0.337) SDCM <5
Initial input power	200 W
Power consumption tolerance	+/-10%
Init. Color Rendering Index Tolerance	+/-2

### Over Time Performance (IEC Compliant)

Control gear failure rate at median useful life 50000 h	5 %
Lumen maintenance at median useful life* 50000 h	80

### Application Conditions


Ambient temperature range	-25 to +40 °C
Performance ambient temperature Tq	25 °C
Maximum dim level	Not applicable

### Product Data

Full product code	871951453341799
Order product name	BVP165 LED240/865 PSU 200W SWB CE
EAN/UPC - Product	8719514533417
Order code	911401868483
Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	4
Material Nr. (12NC)	911401868483
Net Weight (Piece)	4.250 kg



## Dimensional drawing



Ledinaire floodlight BVP105/106

## Ledinaire floodlights gen3

