



Fuse-link, LV, 10 A, AC 550 V, BS88/A1, 14 x 55 mm, gL/gG, BS

**Part no.**                      **10A 550V AC BS88 FUSE**  
                                      **NITD10**

|                      |  |
|----------------------|--|
| Product name         | Eaton Bussmann series low voltage British standard fuse  |
| Part no.             | 10A 550V AC BS88 FUSE                                    |
| EAN                  | 5027590503990  |
| Product Length/Depth | 55 millimetre  |
| Product height       | 14 millimetre  |
| Product width        | 14 millimetre  |
| Product weight       | 15.6 gram  |
| Compliances          | CE Marked<br>RoHS Compliant                              |
| Certifications       | IEC 60269-2<br>BS88                                      |
| Product Tradename    | None   |
| Product Type         | Low voltage British standard fuse                        |
| Product Sub Type     | None   |
| Amperage Rating      | 10 A   |
| Voltage rating       | 550 V  |
| Voltage type         | AC/DC  |
| Breaking capacity    | 80 kA  |
| Class                | Class gG/gL  |
| Application          | general industrial applications                          |
| Fuse type            | NITD   |
| Fuse size            | BS88/A1  |
| Fitted with:         | Offset bolted tags                                       |
| Connection           | Bolt-on  |
| Suitable for         | CM32FC Camaster fuse holder<br>RS20 Red spot fuse holder |

## Technical data ETIM 8.0

|  |    |   |
|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) |    |   |
| Fuse construction type according to IEC 60269  |    | A1  |
| Type of current  |    | AC  |
| Rated voltage AC   | V  | 550   |
| Rated voltage DC   | V  |   |
| Rated current  | A  | 10  |
| Utilization category   |    | gL/gG (cable protection/equipment protection) |
| Breaking capacity  | kA | 80  |
| Colour code  |    | None  |
| Type of fuse status indicator  |    | None  |
| Power loss at rated current  | W  | 2.1   |
| Mounting holes   |    | Other   |
| Centre-to-centre distance of connections   | mm | 42.5  |