



Fuse-link, LV, 4 A, AC 550 V, BS88/A1, 14 x 55 mm, gL/gG, BS

NITD4

Similar to illustration

Product name	Eaton Bussmann series low voltage British standard fuse	
Part no.	NITD4	
EAN	5027590504171	
Product Length/Depth	55 millimetre	
Product height	14 millimetre	
Product width	14 millimetre	
Product weight	14.65 gram	
Compliances	RoHS Compliant CE Marked	
Certifications	BS88 IEC 60269-2	
Product Tradename	None	
Product Type	Low voltage British standard fuse	
Product Sub Type	None	
Amperage Rating	4 A	
Voltage rating	550 V	
Voltage type	AC	
Breaking capacity	80 kA	
Class	Class gG/gL	
Application	general industrial applications	
Fuse type	NITD	
Fuse size	BS88/A1	
Fitted with:	Offset bolted tags	
Connection	Bolt-on	
Suitable for	CM32FC Camaster fuse holder RS20 Red spot fuse holder	

Technical data ETIM 8.0

Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)		
Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011])		
Fuse construction type according to IEC 60269		A1
Type of current		AC
Rated voltage AC	V	550
Rated voltage DC	V	
Rated current	A	4
Utilization category		gL/gG (cable protection/equipment protection)
Breaking capacity	kA	80
Colour code		None
Type of fuse status indicator		None
Power loss at rated current	W	1.4
Mounting holes		Other
Centre-to-centre distance of connections	mm	42.5