



Fuse-link, LV, 6 A, AC 550 V, BS88/A1, 14 x 55 mm, gL/gG, BS

NITD6

|                      |  |  |
|----------------------|--|--|
| Product name         |  | Eaton Bussmann series low voltage British standard fuse  |
| Part no.             |  | NITD6  |
| EAN                  |  | 5027590504188  |
| Product Length/Depth |  | 55 millimetre  |
| Product height       |  | 14 millimetre  |
| Product width        |  | 14 millimetre  |
| Product weight       |  | 15.65 gram   |
| Compliances          |  | CE Marked<br>RoHS Compliant                              |
| Certifications       |  | IEC 60269-2<br>BS88                                      |
| Product Tradename    |  | None   |
| Product Type         |  | Low voltage British standard fuse                        |
| Product Sub Type     |  | None   |
| Amperage Rating      |  | 6 A  |
| Voltage rating       |  | 550 V  |
| Voltage type         |  | AC   |
| Breaking capacity    |  | 80 kA  |
| Class                |  | Class gG/gL  |
| Application          |  | general industrial applications                          |
| Fuse type            |  | NITD   |
| Fuse size            |  | BS88/A1  |
| Fitted with:         |  | Offset bolted tags                                       |
| Connection           |  | Bolt-on  |
| Quantity             |  | 20   |
| Suitable for         |  | CM32FC Camaster fuse holder<br>RS20 Red spot fuse holder |

Technical data ETIM 8.0

|  |    |   |
|--|----|---|
| Circuit breakers and fuses (EG000020) / HRC fuse (EC004556)  |    |   |
| Electric engineering, automation, process control engineering / Electrical installation, device / Safety fuse inserts / Safety fuse inserts (unspecified) (ecl@ss10.0.1-27-14-20-90 [BAB264011]) |    |   |
| Fuse construction type according to IEC 60269  |    | A1  |
| Type of current  |    | AC  |
| Rated voltage AC   | V  | 550   |
| Rated voltage DC   | V  |   |
| Rated current  | A  | 6   |
| Utilization category   |    | gL/gG (cable protection/equipment protection) |
| Breaking capacity  | kA | 80  |
| Colour code  |    | None  |
| Type of fuse status indicator  |    | None  |
| Power loss at rated current  | W  | 1.8   |
| Mounting holes   |    | Other   |
| Centre-to-centre distance of connections   | mm | 42.5  |